

Description	Tierrafino contact serves as a primer/mechanical key for clay plasters and other plasters onto smooth or very absorbing substrates.
Colors	contact is white before and after drying.
Properties	contact is odorless after drying. Do not apply in areas with direct contact with water. contact is damp open and contributes to moisture regulating systems.
Substrates	Dry and free of dust and grease. Roughen very smooth surfaces using sandpaper. Treat highly absorbing surfaces with Tierrafino fix before application of contact .
Circumstances	The air- and substrate temperature must be at least +5°C.
Mixing	Tierrafino contact is ready to use.
Application	contact can be applied with a roller or a brush. To refine the texture gently roll or brush again within a short time after application. Spread sand out equally. Use a good quality masking tape onto substrates and/or onto dried out contact .
Consumption	Ca. 0,25 l/m ² per application onto smooth substrates. Consumption is greater when applied onto very rough substrates.
Drying time	Under normal circumstances (+20°C and 60% air humidity), ipaint is dry between 4 - 12 hours. Hardened out after 2 days.
Thinner	Water. Dilute with max. 5%.
Workability	Once opened, Tierrafino contact must be used within 1 year.
Composition	Tree resin binder, calcium carbonate, titane oxide, water, additives, preservative.
Safety measures	Avoid contact with eyes and mucous membranes. With induced risk (ceilings) wear safety glasses. Keep out of reach from children.
Storage advice	Dry and cool but free of frost.
Packaging	5 & 10 l buckets.

Although this product description has been put together with utmost precision, Tierrafino will not be liable for any indirect or direct damage that may occur, by using the information offered in this product description.

Tierrafino contact

the primer for:

Tierrafino Finish

Tierrafino Base

Tierrafino Kalk