

Description	Tierrafino fix serves as a strengthener for clay plasters and as a sealant for absorbing surfaces. Tierrafino fix mixed with water will settle dusting substrates. Tierrafino fix can be mixed with pigments and water to create veiled layered effects onto Tierrafino Finish and Kalk. Add Tierrafino Finish to fix to create a rough textured paint.
Colors	Tierrafino fix is milky when wet and transparent after drying.
Properties	fix is odorless after drying. Apply in areas with mild contact with water. fix is damp open and contributes to moisture regulating systems.
Substrates	Dry and free of dust and grease.
Circumstances	The air- and substrate temperature must be at least +5°C.
Mixing	Tierrafino fix is ready to mix with water.
Application	There are 3 ways to apply Tierrafino fix to strengthen clay plaster:
Pre mixing	Mix 1 liter Tierrafino fix with 4 liters water, stir it well. Now add 25 kg Tierrafino clay plaster to the mixture and stir well until a spreadable paste is achieved. Apply this mixture to the wall or ceiling as described on the clay plaster application.
After laying on	Mix 1 part Tierrafino fix with 4 parts water in a bucket, stir well. Apply Tierrafino clay plaster as described, after stiffening of the plaster, sponge the clay plaster with the mixture of fix and water. After this treatment, follow the Tierrafino clay plaster manual.
At a later stage	After Tierrafino clay plaster has been applied and successfully finished, Tierrafino fix is applied as followed: Mix 1 part Tierrafino fix with 4 parts warm water, spray regular water onto the finished clay plaster to make it overall equally humid, e.g. the color of the clay plaster must be dark. Do not saturate the plaster, apply only just enough water to have the color change. When the plaster is humid, apply the mixture of water and fix with a sponge by way of very light circular movements onto Tierrafino clay plaster. Now brush Tierrafino clay plaster as described on the Tierrafino clay plaster application page. Instead of using a sponge, a spray may also be used. Note: the second way of applying Tierrafino fix (after laying on) is regarded the most efficient and easy way of application.
Sealant	Apply fix with a brush or a roller to reduce the absorbency partially.
Veiled effect	Tierrafino fix mixed with Tierrafino pigment for a veiled layered effect should be applied on a clay plaster wall with a brush. A less transparent effect can be reached by using a sponge.

Consumption	To strengthen clay plaster approx. 0,2 liter/m ² .
Drying time	Under normal circumstances (+20°C and 60% air humidity), fix is dry between 4 - 12 hours. Hardened out after 2 days.
Thinner	Water.
Workability	Once opened, Tierrafino fix must be used within 2 years.
Composition	Cellulose binder, tree resin binder, water softener, preservative, water.
Safety measures	Avoid contact with eyes and mucous membranes. With induced risk (ceilings) wear safety glasses. Keep out of reach from children.
Storage advice	Dry and cool but free of frost.
Packaging	5 l plastic container.
Although this product description has been put together with utmost precision, Tierrafino will not be liable for any indirect or direct damage that may occur, by using the information offered in this product description.	

